

## **ALUFLEX 80B SLIDING SYSTEM**

Häfele's Sliding Systems have become synonymous with maximum functionality and minimal effort. Constant innovation over the years has enabled us to introduce new and improved fittings that boast of commendable quality, durable build and expert craftmanship. It is hence no wonder that the new Aluflex 80B from Häfele's Slido Range, ranks high on functionality, versatility, design and application.

From offering an elegant access to your walk-in wardrobe set-up to functioning as a captivating partition system between living areas or in commercial spaces, the patented Aluflex 80B aluminium profiled system provides a mesmerising floor to ceiling sliding solution. It can easily support panel weights up to 80 kg and comes with an integrated double-sided soft closing mechanism. Different panel design and material possibilities combined with the attractive anodized black finish of the profiles and tracks helps exude style and sophistication in your surroundings as well as add character and dimension to your interiors.





## **FEATURES**



**Heavy Weight Doors:** The Aluflex Sliding System consists of a bottom track that sustains the door weight and provides additional guidance during the sliding operation. Certified with a cycle testing of 40,000 cycles, this durable system easily carries panel weights up to 80 kg.



**Minimal Design:** The horizontal and vertical profiles provided with the Aluflex system are extremely slim, promising minimal design with functional efficiency.



**Easy Adjustments:** The height of the door can be easily adjusted through the centre drilled hole at the bottom portion of the vertical profile via an Allen key.



**Versatile Applications:** With Aluflex, you can choose wooden panels for privacy, glass panels for complete openness and transparency or a mix of patterned glass and wood to achieve a truly unique look customized by you.



**Soft Opening and Closing:** The patented double-sided soft closing mechanism is a part of the Aluflex 80B System kit and ensures smooth and silent opening and closing on both sides.