

# FIRE RATED DOOR HARDWARE







Ozone continues with the concept of "Total Vision" to create transparent & elegant commercial spaces. Every fitting in our architectural glass hardware range is designed to meet the concept of "Total Vision".

Ozone, a leading name in architectural hardware domain, offers high quality architectural hardware & safety solutions worldwide. It has achieved many accolades internationally for its innovative and technologically advanced products and solutions. Its manufacturing capability enables it to offer turnkey projects of all sizes. The design team includes architects, product designers & structural engineers who innovate and support the customers and project managers. Offering more than 3000 products from its portfolio intelligently divided into 09 broad categories based on application. Ozone has been continuously innovating to offer best solutions complying with international norms of safety & quality.

#### Manufacturing Capability

Our state-of-the-art manufacturing units located in India and overseas enable us to provide Standard and Customized Architectural Hardware & Infrastructural Solutions in Stainless Steel.

#### Our strengths are:

- Over 20 years extensive experience of operating in Architectural Hardware Industry and Digital Safes
- Dedicated 20 years technically experienced team
- Advanced automated machines & tools
- Ability to undertake OEM & ODM projects
- In-house R & D set-up for offering right mix of design, cost, quality and delivery
- Project support & customer service team







Our manufacturing units are equipped with the latest and technologically advanced machines. These comprise CNC laser cutting machine, CNC water jet cutting machine, CNC shearing machine, robotic welding & automatic polishing machines that enable us to manufacture all types of hardware fittings in stainless steel material and finish, standard as well as customized, as per international safety & quality norms.



Scan QR Code for Manufacturing Facility

#### Location:

Kala Amb Himachal Pradesh India




VMC (Vetical Machine Center)



Polishing Machine



CNC Punching Machine



Welding Centre

### **Ozone Product SBUs**

Our product portfolio offers more than 3000 SKUs, intelligently divided into 09 broad categories. We constantly endeavour to innovate products for offering better solutions that deliver enhanced value to our discerning customers world over such as architects, builders, contractors, fabricators, specifiers, consultants and home owners.

#### **OZONE HARDWARE**













## **OZONE METALSCAPES**









## **OZONE SECUTECH**

















## **OVERHEAD DOOR CLOSERS**



**NSK-680 STD SILVER** 

OVERHEAD DOOR CLOSER (SCISSOR ARM)

# Rack and Pinion Overhead Door Closer

#### Adjustable closing force EN 2-4

- Maximum door weight: 80kg
- Finish: Silver/Gold/Brown/Antique Brass



**NSK-780 STD SILVER** 

OVERHEAD DOOR CLOSER (SCISSOR ARM)

#### Rack & Pinion Door Closer with Adjustable closing force EN 2-5

- Maximum door weight: upto 100kg
- Finish: Silver



**NSK-880 STD SILVER** 

OVERHEAD DOOR CLOSER (SCISSOR

#### Rack & Pinion Door Closer with Adjustable closing force EN 2/3/4/5

- Maximum door weight: 100Kg
- Finish: Silver



EN 1154 Tested

5 Lakhs

80 Kg

Capacity

EN 1154 Tested

5 Lakhs

**Cycles Tested** 



**NSK-680A STD SILVER** 

**Power Adjustable** 

OVERHEAD DOOR CLOSER (SCISSOR ARM)

#### Rack and Pinion Door Closer with

# Adjustable closing force EN

- Maximum door weight: 80kg
- Finish: Silver



#### **NSK-780 STD SILVER**

OVERHEAD DOOR CLOSER (SCISSOR ARM)

#### Rack & Pinion Door Closer with Adjustable closing force EN 2-5

- Maximum door weight: upto 100kg
- Finish: Silver







5 Lakhs





EN 1154 Tested









EN 1154 Tested

5 Lakhs



#### **CONCEALED DOOR CLOSERS**



#### CDC-3800 STD SILVER

CONCEALED DOOR CLOSER

#### Concealed Rack & Pinion Door Closer with EN 3

- •Finish: Silver







# CDC-CA-6800 STD SILVER

#### Cam Action Concealed Door Closer with Adjustable Closing Force EN 2-4

- •Minimum Door Thickness: 41mm
- •Maximum door weight: 80kg
- •Finish: Silver













#### •Minimum Door Thickness: 38mm

- •Maximum door weight: 60kg





# **ELECTROMAGNETIC DOOR CLOSERS**



#### **NSK-980-EMHO-TA STD SS**

Door Closer with Electromatic Hold Open Track Arm without Smoke Detector Finish: SSS



#### NSK-980-EMHO-TA-S STD SS

Door Closer with Electromagnetic Hold Open Track Arm with Smoke Detector Finish: SSS



#### NSK-980-EMHO-SA

Door Closer with Electromagnetic Hold Open Scissor Arm without Smoke Detector Finish: SSS



#### NSK-980-EMHO-SA-S

Door Closer with Electromagnetic Hold Open Scissor Arm with Smoke Detector Finish: SSS



# **BUTT HINGE**





**OZ-BHF-2BB 4x3x3 SSS**Fire Rated Butt Hinges With Two Ball Bearings **SS-304** 

# MORTISE LOCK BODY



OML-11A-F 45/85 OML-11A-F 55/72 Fire Rated Mortise Lock Body with Dead Bolt & Latch Bolt







#### OZML-DL1-F 55MM SSS

Fired Rated Closed Body Mortise Lock with Double Throw Dead Bolt







# FIRE RATED PANIC (EXIT) DOOR HARDWARE AND ACCESSORIES

#### PANIC DOOR HARDWARE



Finish: SSS



1 Point Modular

Push Panic Bar for Single Door

OZ-PB-TCR-F-842MM SSS

Max Door Width : Upto 1100

1100


OZ-PB-TCR-F-1020MM SSS

333

Max Door Width : Upto 1400

#### Features:

- Push bar for fire and smoke check doors
- Stainless steel latch and security anti-thrust latch
- Certified as per UL 10C 1-3 HOURS FIRE RATED
  - For Hollow Metal Door: 3 Hours Fire Rated
  - For Wooden Door: 1.5 Hours Fire Rated



Push Panic Bar for Double
Door

OZ-PB-TCV-F-842MM SSS

Max Door Width: 1100/2400

OZ-PB-TCV-F-1020MM SSS

Max Door Width: 1400/2400

#### **Accessories**



**OZ-PB-TCTRIM-F-STD SSS**External Trim



**OZ-PBV-DLS-Std** Overlapping Cover Strike Plate

#### **CROSS PUSH PANIC BAR**



 $\epsilon$ 





#### OZ-PB-CRR-F-900mm Silver

Max Door Width : Upto 1200 Door Height 2300mm

#### Features:


- Cross bar for fire and smoke check doors
- 3 hours fire certified
- Suitable for door Thickness 40-60mm
- Connecting rod length: 900mm
- Compatible with external trim OZ-PB- CRTRIM-F-STD Silver



Finish: SSS

# FIRE RATED PANIC (EXIT) DOOR HARDWARE AND ACCESSORIES

#### FIRE RATED CROSS PUSH PANIC BAR



#### OZ-PB-CRV-F-900mm Silver

Max Door Width: Upto 1200 Door Height 2300mm

#### Features:

- Cross bar for fire and smoke check doors
- 3 hour fire certified
- Suitable for door Thickness 40-60mm
- Connecting rod length: 900mm
- Compatible with external trim OZ-PB- CRTRIM-F-STD Silver

#### **Accessory**



**OZ-PB-CRTRIM-F-STD Silver** External Trim

#### Features:


- Rectangular External Trim with lever handle for fire and smoke check doors
- 3 hour fire certified
- EN-1634-1:2008
- Max Door Thickness: 75mm
- Aluminum material grade
- Powder Coated finish
- Solid Square Spindle
- Master Key available on request Replaceable EP Cylinder with one side key operation
- Ideal for emergency exit of metal/Wooden single/double door

#### FIRE-RATED GRAVITY DOOR COORDINATOR









#### **OZ-GDC-F-STD SILVER**

For sequencing door closing action

#### **Features**

- Sequences the Door Closing i.e. roller arm stops active door from closing before the inactive door
- Gravity action arm and door bracket are adjustable on the jamb for ease of installation
- Nylon roller to enable the inactive door to easily operate

#### **Specifications**

- Device: Non-handed & reversible
- Projection: 6-1/2"
- Material: Forged brass with nylon roller
- Finish: Satin chrome



# PULL HANDLES

# Back to Back Installation Handle SS 304



**OGH-11**Glass door handle back to back installation.



**OGH-55**Glass door handle back to back installation.



OGH-77 Glass door handle back to back installation.



**OGH-88**Glass door handle back to back installation.